

The Perfect Balance of Speed, Size, and Memory



4,980fps @ 1920x1080 | 10GPx/s throughput | 10,000fps @ 1176x870

FEATURES + OPTIONS

- HD resolution 1920 x1080 pixel sensor, more pixels = greater accuracy
- Full resolution to 4,980 frames/second, maintaining higher res at higher speeds
- 8 TB internal SSD capacity
- Up to 144 GB of on-board memory for long recordings or multiple buffers
- Internal or external SSD drive for fast data transfer
- Impressive 10 GP/sec throughput
- Global electronic shutter to 250 ns*
- Compatible with all Nikon F and Canon EF mount lenses
- Record up to 500,000 fps
- App-based tablet control via Controller Display Unit (CDU) for simple operation
- Fully compatible with the i-SPEED Software Suite 2.0 for more advanced functions
- Upgrade path between models

* subject to export regulations

High performance high-speed camera in a compact and durable form-factor.



The sealed electronics design of the i-SPEED 5 utilizes an innovative internal cooling system—drawing heat from the inside of the camera and venting it to the atmosphere

Sublime ease-of-use coupled with full feature functionality



IMAGER

Sensor type	Custom CMOS
Sensor resolution	1920 x 1080 pixel
Sensor size	25.920 mm x 14.580 mm
Sensor diagonal	29.74 mm
Pixel size	13.5 µm
Bit depth	12 bit (36 bit color)
ISO (12232-2:2006, D, sat)	Mono ISO 8,500D (sat) / 68,000D (sat) Color ISO 3,060D (sat) / 24,480D (sat)
Maximum frame rate	500,000 fps
Shutter type	Global exposure
Shutter time, standard	1 µs min (standard)
Shutter time, fast mode	250 ns min (export restricted)

SYNCHRONIZATION and CAPTURE

Trigger	TTL T0 to 0-100%
Trigger modes	Circular, ROC, BROCC
Sync	10 Hz – 350 kHz
Luminance histogram	Iris setting aid tool
i-CHEQ 360	Camera status LEDs
i-FOCUS	Focusing aid tool
i-EXPOSE	High/low exposure highlight
Control	PC or CDUE
IRIG input	IRIG – B to 1 µs
Internal memory	18 GB standard, upgrade to 144 GB

PHYSICAL and ENVIRONMENTAL

Dimensions inches	5.0 (W) x 5.1 (H) x 12.0 (L)
Dimensions mm	127 (W) x 129 (H) x 305 (L)
Weight	9.9 lb (4.5 kg)
Input voltage	14-36 V
Power consumption	110 W nominal, 150 W max
Mounting	1/4 x 20 and 3/8 x 16 tripod plate
Lens mount	Custom, swappable lens plate
EMC	EN55032-A, EN55024
Safety	BS EN61010-1 (camera), IEC60950 (PSU)
CE marking	EMC directive (camera), EMC directive, LV directive (PSU)
Lead free	RoHS directive
WEEE	Compliant
Temperature °F	14° to 122° operation, -4° to 140° storage
Temperature °C	-10° to +50° operation, -20° to 60° storage
Pressure	71 kpa to 106 kpa
Relative humidity	95% at 104°F non-condensing
Power input connector	4 pin Lemo
Trigger input	BNC 75 Ω
I/O connector	10 pin Lemo, trigger in / sync / exposure out / remote power

CONNECTIVITY

Video outputs	HD-SDI, HDMI
USB	USB 3
Network	1Gb/s RJ45 / 10 pin Lemo
Video	IXV, AVI (compressed or uncompressed)
Image sequence	TIFF, JPG, RAW
Ethernet control	1 Gb/s
Remote control	Via supplied software

PC SOFTWARE

Standard control	Control ONE
Premium control	Control MULTI-DAQ
Editing	i-SPEED Movie Maker
Analysis	ProAnalyst® Lite by Xcitex
Viewer	i-SPEED Viewer
Utilities	i-SPEED Lens Calculator, i-SPEED Viewer
Software Developers Kit	C++, LabView
Synchronized data acquisition	USB DAQ, 8 options

PURCHASING OPTIONS

CDUe	Controller Display Unit
Sensor	Color / Mono
Memory	18 GB (std) / 36 GB / 72 GB / 96 GB / 144GB
Shutter time	1 µs (std) / 250 ns (subject to export restrictions)
Internal SSD	500 GB / 1 TB / 2 TB / 4 TB / 8 TB
External SSD	500 GB / 1 TB / 2 TB
Lens mounts	F mount (Nikkor D) / F mount (Nikkor G) C mount / EF mount
Warranty	1 yr (std) / 2 yr / 3 yr
IRIG	IRIG-B

FRAME RATES, RESOLUTION, and DURATION

FPS	Resolution	18GB	36GB	72GB	96GB	144GB
100	1920x1080	30.4 sec	60.9 sec	122 sec	162 sec	243 sec
200	1920x1080	15.2 sec	30.4 sec	61 sec	81 sec	122 sec
300	1920x1080	10.1 sec	20.3 sec	41 sec	54.1 sec	81.1 sec
500	1920x1080	6.1 sec	12.2 sec	24 sec	32.5 sec	49 sec
1,000	1920x1080	3 sec	6.1 sec	12 sec	16.2 sec	24.3 sec
2,000	1920x1080	1.5 sec	3 sec	6.1 sec	8.1 sec	12.2 sec
3,000	1920x1080	1 sec	2 sec	4.1 sec	5.4 sec	8.1 sec
3,985	1920x1080	0.8 sec	1.5 sec	3.1 sec	4.1 sec	6.1 sec
4,980	1920x1080	0.6 sec	1.2 sec	2.4 sec	3.3 sec	4.9 sec
5,000	1904x1080	0.6 sec	1.3 sec	2.5 sec	3.3 sec	5 sec
6,382	1512x1080	0.6 sec	1.2 sec	2.5 sec	3.3 sec	5 sec
7,500	1344x1008	0.6 sec	1.3 sec	2.5 sec	3.4 sec	5.1 sec
10,000	1176x870	0.6 sec	1.3 sec	2.5 sec	3.4 sec	5 sec
15,000	952x708	0.6 sec	1.3 sec	2.5 sec	3.4 sec	5.1 sec
20,000	840x594	0.7 sec	1.3 sec	2.6 sec	3.4 sec	5.2 sec
50,000	504x366	0.7 sec	1.4 sec	2.8 sec	3.7 sec	5.6 sec
100,000	392x204	0.8 sec	1.6 sec	3.2 sec	4.3 sec	6.4 sec
200,000	392x90	0.9 sec	1.8 sec	3.7 sec	4.9 sec	7.3 sec
300,000	392x54	1 sec	2 sec	4.1 sec	5.4 sec	8.1 sec
500,000	392x24	1.4 sec	2.7 sec	5.5 sec	7.3 sec	10.9 sec

Note: Other resolutions and speeds are available.



info@ix-cameras.com • ix-cameras.com

Specifications subject to change
Document: DS-508-10.3.18 Copyright © 2018 iX Cameras Ltd.

United Kingdom

iX Cameras
Bradley House
Locks Hill
Rochford
Essex, S54 1BB
T: +44 (0) 1702 540 669

United States

iX Cameras
8 Cabot Rd.
Suite 1800
Woburn,
MA, 01801
T: 339 645 0778

China

iX Cameras
Room 1402, Unit 65,
No 399 Hangting Road,
Oriental Hong Jing Garden,
ZhuQiao Town, Shanghai,
T: +86 186 215 60553

India

iX Cameras
J2-101
Swiss County Thergaon
Pune,
411033
T: 0955 256 5021